

Technical Features

	C360	C400	C450
PRODUCTIVITY:			
Embossing Speed	240 plates per hour (40 characters per plate)	240 plates per hour (40 characters per plate)	240 plates per hour (40 characters per plate)
PLATE HANDLING:			
Automatic Input Hopper capacity	N/A	250 plates with 0,50 mm. thickness	500 plates with 0,50 mm. thickness
Loading Device	manual feed	automatic variable hopper	automatic variable hopper
Unloading Device	manual	automatic variable FIFO elevator or side eject	automatic variable FIFO elevator or side eject
EMBOSSING SPECIFICATION:			
Plate Thickness	max. 0,9 mm.	max.0,9 mm.	max.0,9 mm.
Minimum plate dimension (WxD)	30 x 20 mm.	30 x 20 mm.	30 x 20 mm.
Maximum plate dimension (WxD)	150 x 90 mm.	120 x 90 mm.	120 x 60 mm.
Max. Embossing Area	120 x 86 mm.	120 x 86 mm.	120 x 56 mm.
Min. Embossing Area	30 x 16 mm.	30 x 16 mm.	30 x 16 mm.
Available Embossing Drums	50/60/100 ch.or 93 ch. + 3 slots for logos, automotive and other special drums upon request	50/60/100 ch.or 93 ch. + 3 slots for logos, automotive and other special drums upon request	50/60/100 ch.or 93 ch. + 3 slots for logos, automotive and other special drums upon request
Maximum Logo Size	6,6 x 6,6 mm.	6,6 x 6,6 mm.	6,6 x 6,6 mm.
Standard Type Set	Simplex 2 (350) - 3,5 mm. embossing	Simplex 2 (350) - 3,5 mm. embossing	Simplex 2 (350) - 3,5 mm. embossing
Optional Type Sets	Simplex 3 (489) - 4.1 mm. embossing Blocco USA (490) - 4.1 mm. embossing Blocco (488) - 5 mm. embossing Doppio Blocco (511) - 6,1 mm. embossing Doppio Blocco Lungo (611) - 8,2 mm. embossing Maxi Blocco - 12,2 mm. embossing Elite Dog Tag (328) - 3,5 mm. debossing Ford automotive (311) - embossing Simplex 1 (111) - indent Simplex 2 (350) - indent Reversed types upon request Special sets/type upon request Logos upon request	Simplex 3 (489) - 4.1 mm. embossing Blocco USA (490) - 4.1 mm. embossing Blocco (488) - 5 mm. embossing Doppio Blocco (511) - 6,1 mm. embossing Doppio Blocco Lungo (611) - 8,2 mm. embossing Maxi Blocco - 12,2 mm. embossing Elite Dog Tag (328) - 3,5 mm. debossing Ford automotive (311) - embossing Simplex 1 (111) - indent Simplex 2 (350) - indent Reversed types upon request Special sets/type upon request Logos upon request	Simplex 3 (489) - 4.1 mm. embossing Blocco USA (490) - 4.1 mm. embossing Blocco (488) - 5 mm. embossing Doppio Blocco (511) - 6,1 mm. embossing Doppio Blocco Lungo (611) - 8,2 mm. embossing Maxi Blocco - 12,2 mm. embossing Elite Dog Tag (328) - 3,5 mm. debossing Ford automotive (311) - embossing Simplex 1 (111) - indent Simplex 2 (350) - indent Reversed types upon request Special sets/type upon request Logos upon request
COMUNICATION:			
Interface	serial RS232	serial RS232	serial RS232
Protocols	Xon-Xoff multiembosser pound-pound	Xon-Xoff multiembosser pound-pound	Xon-Xoff multiembosser pound-pound
User and Diagnostic Software	MatiCard	MatiCard	MatiCard
OTHER OPTIONS:	standard Pc keyboard special barcode type emergency "Panic Button" current loop interface parallel centronics interface	standard Pc keyboard special barcode type emergency "Panic Button" current loop interface parallel centronics interface	standard Pc keyboard special barcode type emergency "Panic Button" current loop interface parallel centronics interface
DIMENSIONS AND WEIGHT:			
Dimensions (WxDxH)	500 x 500 x 371 mm.	800 x 500 x 371 mm.	800 x 500 x 440 mm.
Weight	50 Kg.	70 Kg.	75 Kg.
POWER REQUIREMENTS:			
Electrical requirements	110V, 220V 50/60Hz	110V, 220V 50/60Hz	110V, 220V 50/60Hz