

M-Series M10



PRECISION AND CONVENIENCE IN PERSONALIZATION

- 60 character capacity drum with numbers and punctuation marks
- Automatic interspacing and free format on whole plate
- Correction device
- Manually operated

Used for:

- MILITARY ID TAGS
- CABLE/HOSE TAGS
- INVENTORY/ASSET CONTROL & TRACKING TAGS FOR HARSH ENVIRONMENTS
- WORK IN PROGRESS COMPONENTS IDENTIFICATION
- TAGS FOR GALVANIZED OR HEAT - TREATED PROCESSES
- SERIAL NUMBER TAGS

Used by:

- Automotive Factories
- Shipyards
- Steel Plants
- Army
- White Goods Manufacturers
- Motor Manufacturers
- Tire Manufacturers
- Lift Manufacturers
- Crane Manufacturers
- Fire Door Manufacturers
- Pump Manufacturers
- Logging Industries
- Logistical Management

Available Fonts	Embossing: Simplex 2, Block, Block USA, OCR B1. Debossing: Dog -Tag
Embossing area	Up to 63 mm from the top edge of the plate leaving free 4 mm from the bottom. Measurements are defined according to the base of the character
Physical dimensions	382mm x 412mm x 312mm; 20kg.
Plate Dimensions	Width: min 30 mm – max 115 mm Height: min 20 mm – max 90 mm Thickness: from 0.4 to 0.9 mm